



VILLAGIO FLOORS, INC.  
TOLL FREE: 888.488.3331 Fax: 323.406.8207  
VILLAGIOWOODFLOORS.COM

## Care and Maintenance

Keep in mind, like any floor covering, hardwood floors will show signs of wear over time. Flooring should be one of the last items installed in a project. In order to protect the floors while other trades are finishing their work prior to final cleanup and turnover to the owner, use a breathable protective covering such as Ram Board or Floorotex. Do not use Red Rosin paper, as it may discolor the finish, and do not use polyfilm or other non-breathing coverings as they can cause damage from humidity buildup. Clean the floor thoroughly before laying the covering to ensure that no debris is trapped underneath. Tape pieces of protective covering together but do not tape them to the wood flooring. By observing a few precautions and setting up a regular cleaning routine/maintenance program, you can expect years of beauty from your floor. The following are examples of the simple and necessary maintenance you should perform to help keep your floors looking great.

- ❖ Dirt, grit and sand act like sandpaper to scratch, dent and dull hardwood floors. You should place floor mats at exterior entrances to trap dirt, they should be moved occasionally to allow natural color changes caused by light to occur evenly in all areas. This is especially important over the first few months the flooring is installed.
- ❖ Avoid walking on floor with high heels or spiked shoes, not doing so could damage even the hardest woods and finishes.
- ❖ Work boots and shoes that may have pebbles lodged in the soles should be removed prior to entering.
- ❖ Sweep, vacuum or dust mop at least weekly since built-up grit can damage the surface of the wood; most damage to wood floor finishes is caused by debris that is walked on.
- ❖ The vacuum head should be a soft brush or felt type to avoid scratching. Be certain the wheels of the vacuum are clean and that they roll softly so that they do not damage the finish. **DO NOT USE A VACUUM WITH A BEATER BAR HEAD .**
- ❖ Use area rugs in high traffic areas and pivot points (e.g., stair landings, room entries, etc.), especially if you have a large family or indoor pets. Do not allow soiled mats or rugs to stay on the floor as they can trap moisture on the surface and wear through a finish over time.
- ❖ Rubber backed rugs are not recommended as discoloration may occur due to plasticizers migrating out of some rug backings. Instead, rubber liners/pads that are made especially for rugs over hardwood floors are recommended. These liners also have holes in them for the wood to breathe and can be found at your local home improvement and some hardwood flooring stores.



VILLAGIO FLOORS, INC.  
TOLL FREE: 888.488.3331 Fax: 323.406.8207  
VILLAGIOWOODFLOORS.COM

- ❖ Remove all spills promptly using a soft cloth and recommended cleaning products. Any spills with acidic properties like pet urine, soda, etc. should especially be cleaned as soon as possible. Long periods of time uncleaned will likely damage your floor.
- ❖ NEVER drench-map, wet-map, or flood your floor with water or other products. This can severely damage the flooring and will void all warranties. With water or any other cleaning agent, be sure to thoroughly ring out the applicator or mop prior to applying it to the floor. A damp mop is fine as long as the moisture is limited to an amount that will evaporate almost immediately. Moisture that is allowed to seep into the seams between the planks may cause damage to your flooring. The use of a Swiffer® or other similar product that is lightly dampened is highly recommended. Always make sure to wipe dry any excess moisture.
- ❖ Do not use hardwood floor cleaning machines. Use approved maintenance and floor-care products from companies such as Woca and Bona for your oil or lacquer finished floors (contact your local retailer or Villagio Floors, Inc. at 888.488.3331 / info@VillagioWoodFloors.com to discuss which product best suits your need).
- ❖ Keep pets' nails trimmed, and paws clean and free of dirt, gravel, grease, oil, and stains, etc.
- ❖ Place protective pads beneath furniture legs and feet to reduce scratches and dents.
- ❖ Remove any buttons or caps from the feet of chairs/tables and replace with felt.
- ❖ Use a dolly and protective sheets of plywood when moving heavy objects, furniture or appliances.
- ❖ Make certain furniture casters are clean and operate properly (a minimum 1" width is recommended). Rubber casters are recommended as plastic wheels can trap in dirt.
- ❖ Exposure to the sun and its UV rays accelerates the oxidation and aging of wood and fabrics. This causes the stain and/or wood to fade and change color. We recommend closing curtains and blinds or adding sheer drapes to protect the floor from intense and direct sunlight. Rearrange rugs and furniture periodically so that the floor ages evenly. The warranty does not cover damage from the sun and its UV rays.

### Oil Finished Flooring

While all Villagio oil finished floors are prefinished and ready for use, applying a fresh coat of oil to your newly installed floors is strongly recommended; this will add protection and help build a timeline for future maintenance.

Initial Oiling - Once your new oil finished wood flooring has been installed, vacuum up any dust/dirt from the installation process and then clean with WOCA Natural Soap (for a more durable coat you may use WOCA Oil Refresher). Should light



VILLAGIO FLOORS, INC.  
TOLL FREE: 888.488.3331 Fax: 323.406.8207  
VILLAGIOWOODFLOORS.COM

commercial protection be desired WCCA Maintenance Oil can be used in place of the WCCA Oil Refresher. For flooring that is unfinished or will see high traffic regularly WCCA Master Oil is our recommended commercial grade, oil finish.

Continued Maintenance - Simple vacuuming / sweeping on a regular basis and using WCCA Natural Soap for a deeper clean (See instructions below). Swiffers and well rung out rags are acceptable methods of cleaning as well. **Never** repeatedly hard scrub an oil finished floor, to remove stains use WCCA Natural Soap by scrubbing the affected area lightly with a rag or soft bristle brush. WCCA Spot Remover can be used for overly stubborn stains but only as a last resort.

For added protection, and on a quarterly basis, WCCA Oil Refresher can be used to clean and re-oil the surface of your oiled wood floor; this will help lengthen the intervals between maintenance re-oiling. \*Mainly used for light commercial spaces, for residential this may be reduced to twice a year and only if needed.

Because of the availability of spot treatments of oiled wood floors, sanding and refinishing of an aging oiled floor is pretty much unnecessary. However, oil finished wood flooring will start to show wear due to habitual residential traffic patterns. This can be remedied by re-applying an oil to your wood flooring. This is something that is typically done every few years in residential settings and once a year in commercial settings. WCCA Maintenance Oil is recommended for commercial use and WCCA Oil Refresher is recommended for residential use.

Although the oil finish on a wood floor will bead up liquid spills and protect the wood from moisture, it's important to wipe up spills right away. Standing water for any amount of time is not good for wood flooring, regardless the finish type.

**WCCA Natural Soap** – Needs to be diluted in water (3 oz per 1 gallon) prior to mopping your oil finished wood floor. Work with two buckets: one with the soap mix and the other with clean water for rinsing. Mop the soap mix onto your oiled floor (with as little water transfer as possible). After letting the soap sit briefly on the oiled wood floor to dissolve any dirt, make sure to clean up any dirty soap water with your wrung-out mop. After cleaning, let floors dry for 30 minutes before walking on them. Do not exceed use beyond 1 - 2 times a month (or as needed). Please see water to soap ratio on bottle.

**WCCA Refresher Oil** -Similar to the Natural Soap - dilute and use two buckets, work in sections and allow the newly cleaned oil floor to dry before walking on it; dry time is approximately two hours. For commercial applications, the Oil Refresher can be used on a monthly basis. Please see water to oil ratio on bottle.

**WCCA Maintenance Oil** – Using either a polishing machine or a roller (for manual application), working in sections, make sure to saturate the surface of the wood floor and polish it into the wood. Once the floor looks evenly coated, use cotton cloths to wipe the section. Continue from section to section until the entire wood floor surface has been covered. The



VILLAGIO FLOORS, INC.  
TOLL FREE: 888.488.3331 Fax: 323.406.8207  
VILLAGIOWOODFLOORS.COM

Maintenance Oil takes approximately 4 to 6 hours to dry if done with a polishing machine and approximately 24 hours to dry if applied manually. Proceed to walk on the newly oiled floor with caution. The entire floor should be fully hardened after 3 days. This is an oxidizing oil, opening the windows will allow for faster curing. Please see water to oil ratio on bottle.

**WCCA Master Oil** – Consult Professional

**WCCA Spot Remover / Wood Cleaner**- Spray evenly right onto the stain, let it sit for 10 to 15 minutes while it dissolves then scrub the spot until the stain is removed. Finish by wiping with a damp cloth and then re-oiling the surface of the flooring. Removes blood, coffee, wine and more. **DO NOT** let sit for longer than 20 minutes or it may be necessary to add master oil afterward.

\* Do not use any cleaners or maintenance products on your oil finished wood flooring that aren't specifically made for oil finished wood flooring. This especially refers to products featuring waxes, ammonia, vinegar, detergents or bleach. Cleaners for oil finished wood floors and urethane finished (or similar) wood floors are different. Oil cleaners and maintenance products should not be used on urethane finished (or similar) flooring and vice versa.

\* Protect the surface of your oiled wood floor by using mats at doors leading to the outside, rug pads, and chair glides.

\* Never use tape or any other adhesive products on your oiled wood floor.

### Don'ts

- Drag sharp wooden legs or metal furniture legs as it can scratch/dent hardwood floors.
- Expose to direct sunlight for extended period of time as it may dry/fade natural wood.
- Use steam cleaners. They are not recommended for use on natural wood flooring.
- Avoid mopping the floor with just water. Always use WCCA Soap or Oil Refresher. Standing water can dull a finish, damage the wood and leave a discoloring residue
- Place porous flower pots or vases on the floor.
- Use steel wool or scourers.
- Move heavy furniture without protecting wood flooring by slipping a piece of cloth or pile under the legs or bottom of items.



VILLAGIO FLOORS, INC.  
TOLL FREE: 888.488.3331 Fax: 323.406.8207  
VILLAGIOWOODFLOORS.COM

- WCCA Wood Cleaner is not intended for regular cleaning. It is an aggressive cleaner that strips some of the oil from the floor. Other than using it for small repairs as described above, do not use WCCA Wood Cleaner unless you are preparing the floor for a new coat of oil.

### IMPORTANT

- ❖ Do NOT wash or scrub the flooring for at least 5 days after the installation. This will allow the planks to become "seated" in the adhesive and prevent excess moisture and cleaning agents from interfering with the adhesive bond.
- ❖ Do not use household cleaners that contain lemon oil, tung oil, silicon or ammonia since the warranty will not cover damage caused by non-recommended products. Use of these and other such products will harm the long-term performance of your floor and may also affect its recoat ability.
- ❖ Apply a new coat of WCCA Maintenance Oil (or similar) to your oil finished floors shortly after installation, this will help protect from over-drying and other potential damages. Refreshing an oil finished floor thereafter is recommended every 6 - 36 months (or as needed); a sealer may be used in an effort to reduce upkeep. Please confer with your licensed installer about options.

### SEASONAL GAPS

- ❖ Seasonal gapping can be expected, especially on wider planks. This is normal and not a defect. Throughout its life, wood will naturally expand and contract in response to the wet & dry seasons and also from the environmental conditions in the home. To keep these dimensional changes to a minimum, maintain the home temperature at 60° to 80°F & relative humidity within the range of 30%-50%.

### SURFACE CHECKS

During the winter months of low humidity, minor surface cracks (checks) may appear in wood flooring, then often close up again in the summer months when the humidity is higher. This is a normal characteristic of natural wood and not a basis of a complaint against the manufacturer, especially if there is no structural failure.



VILLAGIO FLOORS, INC.  
TOLL FREE: 888.488.3331 Fax: 323.406.8207  
VILLAGIOWOODFLOORS.COM

## RECOMMENDATIONS

Oil finished floors: For regular cleaning use Woca Natural Soap and soft bristle brooms, no hard-chemical cleaners should be used. Avoid vacuums with beater heads and under **no circumstances** should a steam cleaner be used. Recondition your floors every 6 - 36 months (or as needed) using Woca Oil Refresher (residential) or Woca Maintenance Oil (light commercial), this can be done without a professional, for instructions see back label or visit [www.WocaDirect.com](http://www.WocaDirect.com). With proper maintenance, refinishing must be done by a licensed professional every 7-10 years (residential) or as needed. Please follow all National Wood Flooring Association guidelines which can be viewed at [www.nwfa.org](http://www.nwfa.org).

Lacquer finished floors: For regular cleaning use Swiffer pads, damp rags and soft bristle brooms, no hard-chemical or abrasive cleaners should be used. Avoid vacuums with beater heads and under **no circumstances** should a steam cleaner be used. With proper care, refinishing must be done by a licensed professional every 6 - 8 years (residential use) or as needed. Please follow all National Wood Flooring Association guidelines which can be viewed at [www.nwfa.org](http://www.nwfa.org).

By following these few simple steps today, you can and minimize the need for repairs allowing you  
enjoy your new Villagio Wood Floors for years to come!